





# REVO

Power : 30W / 40W    60W / 80W    90W  
Length : 1188mm    2365mm    3540mm

## Smart Pendant

REVO is a fresh new lighting solution when projecting the interior of an office or any commercial space. Its high-quality housing in powder coated finish makes it a bold and stylish luminaire, available with various optic solutions ; reflector (modular), opal, prismatic or asymmetric; and direct / indirect light distribution. Used as an individual profile or put together in continuous lines or shapes.






## REVO

### MINIMALIST

Revo impresses with its up to 3.5 meters long elegant housing, bringing you more quality light with cost-savings.

Due to its length and low UGR, it delivers a homogenous and efficient distribution of light that enables less luminaires per room. Therefore, it is most suitable for open-space offices, corridors, foyers, conference rooms, institutions and other spacious environments.



# REVO

## Flexible Design Multiple Applications

Revo luminaire is a versatile solution for projects that demand high quality of the lighting system and high visual comfort. With its modular design, the Revo can be used as an individual fixture or as a combination of luminaires put together in continuous lines.

# K-LITE

## REVO DOT-Y

Power : 24W 48W 30W 60W  
 Length: Ø744mm Ø1332mm Ø744mm Ø1332mm



### Features

- NICHIA LED's
- 3000K / 4000K / 5700K or TW 2700K to 5700K
- Ra>80 (>90 On Request)
- SDCM ≤ 3
- L70 / B10 @ 60,000 Hrs
- Standard suspension kit 1M




### Options

- Through wiring
- Dimmable options




L2: Vacuum Metalized Chrome Finish, UGR <12

Beam Angle





PENDANT - LENS

PENDANT - DIFFUSER



Dimension in mm




Housing Colour

- High-quality aluminium with powder coated finish in RAL9005 Black fine texture | RAL9016 White fine texture | RAL9006 Grey fine texture

Light Distribution refer online



L2



### Technical Specifications

#### General

Driver : Constant Current  
 Input Voltage : 220-240Vac  
 Operating Temperature : +25°C~+55°C

#### Light Source

Light Source : NICHIA  
 CRI (Ra) : >80 (>90 On Request)  
 LED Colour Temperature : 3000K / 4000K / 5700K

#### Optical

Efficiency : >90%  
 Tilt : Fixed  
 Beam Angle : 34°, 48°  
 Diffuser/Lens Material : Polycarbonate  
 Secondary Reflector : Vacuum Metalized Chrome Finish  
 UGR : <12

#### Physical

Body : High-Grade Aluminium with Endcaps  
 Mounting : Suspended  
 Finish : White(RAL9016)  
 Black(RAL9005)  
 Grey (RAL 9006)

#### Driver

Power Supply : Integral  
 Power Factor : >0.90  
 THD : <10%  
 Surge Protection : 3KV  
 Efficiency : >85%

### Ordering Guide

#### Pendant - Lens

| ID   | Wattage | Dimension (mm)  |
|------|---------|-----------------|
| 3511 | 24W     | Ø744 x 36 x 76  |
| 3512 | 48W     | Ø1332 x 36 x 76 |

#### Pendant - Diffuser

| ID   | Wattage | Dimension (mm)  |
|------|---------|-----------------|
| 3513 | 30W     | Ø744 x 50 x 70  |
| 3514 | 60W     | Ø1332 x 50 x 70 |