

A premium surface and pendant-mountable linear LED luminaire featuring a robust housing. Engineered for seamless architectural integration, it delivers smooth, hot-spot-free illumination with excellent glare control. High-efficiency satin acrylic diffuser, it is the perfect choice for modern offices, corridors, and commercial spaces seeking a balance of minimalist design and high performance.

MATERIAL

Body	: CRCA housing
Ingress Protection	: IP54
Diffuser	: Satin Acrylic
Mounting	: Ceiling Surface / Pendant

ELECTRICAL

Driver	: Standard
Power Supply	: Integral
Input Voltage	: 230-240Vac / 50-60 Hz
Surge	: 4KV



PRODUCT CONFIGURATIONS

Wattage Range	: 80W - 150W
Optical Beam Angle	: 120°
Light Source	: LUMILEDS
CRI (RA)	: 80
CCT	: 2700K / 3000K / 4000K / 5700K
LED Life Time	: L70 B10 60,000 H

AREA OF APPLICATION

Office, Retail Sector, Receptions, Software industry, Commercial & Business Centers.

AVAILABLE FINISH

White epoxy polyester powder coating





Technical Specifications

General

ID	: 21788
Product Wattage	: 120W
Driver Integrated	: Constant Current
Operating Voltage	: 198-264Vac
Operating Temperature	: -15°~+50°C

Physical

Body	: CRCA housing
Diffuser	: Satin Acrylic
Mounting	: Ceiling Surface / Pendant
Finish	: White epoxy polyester powder coating

Light Source


Light Source	: LUMILEDS
CRI (Ra)	: >80
LED Colour Temperature	: 2700K / 3000K / 4000K / 5700K

Driver

Power Supply	: Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60Hz
Power Factor	: >0.90
THD	: <10%
Surge Protection	: 4kV
Efficiency	: >80%

Optical Performance

Optical Beam Angle	: 120°
--------------------	--------



IP54

