



Technical Specifications

General

Driver : Constant Current
 Input Voltage : 220-240Vac
 Operating Temperature : -15°C~+50°C

Light Source

Light Source : Nichia
 CRI (Ra) : >80 (>90 On Request)
 LED Colour Temperature : 2700K / 3000K / 4000K
 5700K

Optical

Efficiency : >90%
 Tilt : Fixed
 Beam Angle : 50°
 Diffuser/Lens Material : Polycarbonate
 Secondary Reflector : Hexa-Cell (Matte Black)
 UGR : <16

Physical

Body : Extruded Aluminium
 with Die-cast Endcaps
 Mounting : Surface / Pendant
 Finish : RAL 9004 Signal black
 RAL 9016 Traffic White
 RAL 9007 Grey aluminium

Driver

Power Supply : Integral
 Power Factor : >0.90
 THD : <10%
 Surge Protection : 4KV-6KV
 Efficiency : >85%



Ordering Guide

Pendant - Direct / Surface

ID	Wattage	Dimension (mm)
3465	Upto 40W	1188 x 36 x 75
3465	Upto 80W	2365 x 36 x 75
3465	Upto 120W	3540 x 36 x 75

Pendant - Direct & Indirect

ID	Wattage	Dimension (mm)
3465	Upto 40W & 15W	1188 x 36 x 75
3465	Upto 80W & 30W	2365 x 36 x 75
3465	Upto 120W & 45W	3540 x 36 x 75