

## Technical Specifications

### General

ID	: 2769
System Wattage	: 24W LED
Driver Integral	: Constant Current
Operating Voltage	: 100-277Vac
Operating Temperature	: -15°C~+50°C

### Physical

Body	: Die-Cast Aluminium
Diffuser	: Satin Acrylic
Gasket	: Silicone
Mounting Sleeve	: ABS Plastic
Mounting	: Wall - Recess
COD (mm)	: 479 x 83 x 71
Finish	: Powder coated RAL 9004 Signal black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey

### Light Source


Light Source	: NICHIA
CRI (Ra)	: ≥80 ( >90 - On Request )
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K

### Driver


Power Supply	: Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60 Hz
Power Factor	: ≥0.90
THD	: <10%
Surge Protection	: 4KV
Efficiency	: >85%

### Optical Performance

Light Distribution	: Asymmetrical
--------------------	----------------



## Light Distribution



Applied Photometry : H=0.75m

### Note:

- Recessed floor washer.
- Recommended installation height : 600 - 750 mm
- Recommended spacing : 4 metres

**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at [www.klite.in](http://www.klite.in)