K-Lite

Micro LED







OPEN SOURCE

General ID System Wattage	: 4085 : 1W LED	Light Source Light Source CRI (Ra)	: NICHIA : ≥80
Driver Non-Integral Operating Voltage Operating Temperature	: Constant Voltage : 24Vdc :-15°C~+50°C	LED Colour Temperature	
Physical		Driver	
,		Power Supply	: Non Integral
Body & Front Ring Diffuser	: 316 Grade Stainless Steel : Clear / Prismatic / Opal Toughened Glass	Optical Performance	
Mounting Sleeve Mounting	: Polypropylene Black : Wall / Floor - Recess	Beam Angle	: 40°

⊢Ø34 –	_
	41

	Ω	62



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in

K-Lite

Micro LED







OPEN SOURCE

Technical Specif	ications	Light Source	
ID System Wattage Driver Non-Integral Operating Voltage Operating Temperature	: 4085 : 1W LED : Constant Current : 150-270Vac :-15°C~+50°C	Light Source CRI (Ra) LED Colour Temperature	: NICHIA : ≥80 : 2700K / 3000K / 4000K 5700K
Physical Body & Front Ring Diffuser	: 316 Grade Stainless Steel : Clear / Prismatic / Opal Toughened Glass : Polypropylene Black : Wall / Floor - Recess	Driver Power Supply Input Voltage Frequency	: Non Integral : 230-240Vac : 50-60 Hz
Mounting Sleeve Mounting		Optical Performance Beam Angle	: : 40°
§ (€ = 1P6	7 IK08		



٦	_		Γ
			62
			62



Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in