



OPEN SOURCE

Technical Specifications

General

ID	: 4086
System Wattage	: 3W LED
Driver Non-Integral	: Constant Current
Operating Voltage	: 150-270Vac
Operating Temperature	: -15°C~+50°C

Physical

Body & Front Ring	: 316 Grade Stainless Steel
Diffuser	: Clear / Prismatic / Opal Toughened Glass
Mounting Sleeve	: Polypropylene Black
Mounting	: Wall / Floor - Recess

Light Source




Light Source	: NICHIA
CRI (Ra)	: ≥80
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K

Driver

Power Supply	: Non Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60 Hz

Optical Performance

Beam Angle	: 8°/12°/24°/40°/60°/40°x11°
------------	------------------------------



Mounting Sleeve

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in



OPEN SOURCE

Technical Specifications

General

ID	: 4086
System Wattage	: 3W LED
Driver Non-Integral	: Constant Voltage
Operating Voltage	: 24Vdc
Operating Temperature	: -15°C~+50°C

Physical

Body & Front Ring	: 316 Grade Stainless Steel
Diffuser	: Clear / Prismatic / Opal Toughened Glass
Mounting Sleeve	: Polypropylene Black
Mounting	: Wall / Floor - Recess

Light Source




Light Source	: NICHIA
CRI (Ra)	: ≥80
LED Colour Temperature	: 2700K / 3000K / 4000K 5700K

Driver

Power Supply	: Non Integral
--------------	----------------

Optical Performance

Beam Angle	: 8°/12°/24°/40°/60°/40°x11°
------------	------------------------------



Mounting Sleeve

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at www.klite.in